



UPC Code: 07847799618

Country Of Origin : Mexico

# LP220-BPD

20 Space Indoor Load Center with 200A Main Circuit Breaker

Indoor Load Center with 200A Main Circuit Breaker Factory Installed, 20 Spaces, NEMA 1 Rated. Includes Enclosure and Interior Only. Door Sold Separately.

- EASY Leviton's revolutionary design allows the entire Load Center to be wired at rough-in without any circuit breakers present
- SUPERIOR CONDUCTIVITY All Leviton Load Centers come standard equipped with tin plated copper bussing
- ORGANIZED Notches stamped into the enclosure for cable ties promote secure and neat wiring
- MODERN DESIGN Features a white, powder coated finish for a sleek, modern appearance

Learn more about Leviton's electrical wiring devices in ARCAT's construction specifications. \*For applications up to 60A when using copper wire; or 50A when using aluminum wire \*Designed for Leviton Circuit Breakers

#### **Technical Information**

Electrical Specifications	Environmental Specifications
Amperage : 200 A	NEMA Enclosure Type : NEMA 1 Indoor
<b>Operating Temperature :</b> -40C to +70C	
Short Circuit Current Rating : 22 KA	
Spaces / Circuits : 20 / 20	
<b>Type of Load Center :</b> Main Breaker	
Voltage : 120/240 VAC	
Mechanical Specifications	Product Features
Busbar Material : Copper, Bright Tin-Plated	Color : White
	Warranty: 10-Year Limited
Busbar Rating : 225A	
<b>Dimensions :</b> 30" H x 14.25" W x 4" D	
Enclosure Material : Galvanized Steel, White Powder Coat	
Crowned Composition + 4 AVA/C	

Ground Connection : 4 AWG - 2/0 AWG Cu/Al

Supply Connections : 3 AWG - 300 MCM Cu/Al

Weight: 26 lbs.

Standards & Certifications UL 50 : Yes UL 50E : Yes UL 67 : Yes UL 869A : Yes

### Patents


US10658142

US10971319

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

## **Dimensional Drawing**

#### **Cover Screw Dimensions**



#### SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

#### Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

#### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · <u>www.leviton.com/canada</u>

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · <u>www.leviton.com.mx</u>

#### Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: <a href="https://www.leviton.com/international/contacts">www.leviton.com/international/contacts</a>

## © 2024 Leviton Manufacturing Co., Inc.